



Great tool balance and Lightweight

Overhead applications

Compact tool body

BL MOTOR

Compact motor section with overall length of 4-5/8"

Excellent tool balance allows for operation with less wrist fatigue.

Stationary applications

Performs stable cutting even on the floor

Blade cover
Can be used as a rod support.

Rod guide There are two rod guide positions.

◀ [1]
Size of threaded rod
3/8"

◀ [2]
Size of threaded rod
5/16", 1/4"

Cutting capacities Mild steel : 1/4", 5/16", 3/8"
Stainless steel : 1/4", 5/16", 3/8"

High productivity per charge

Work volume on a single full battery charge (with BL1850B)

5/16" Mild steel about 2,300 rods	5/16" Stainless about 1,900 rods	3/8" Mild steel about 1,500 rods
---------------------------------------------	--------------------------------------------	--------------------------------------------

Long life cutter blade

- High rigidity
- Double-edged blade

Both fixed blade and movable blade are double-edged and can be reversed as "new" ones.



Clean cut surface

Burr-free cuts allow for easy nut tightening.



LED job light

Automatic blade stop mechanism

When the blade reaches full open position, it does not close even if the switch trigger keeps being pulled.

Reversing switch lever

1. Cutting position
2. Lock position
3. Reversing position

Convenient metal hook

Guide scale

Rod guide