



5.5 HP Gas Air Compressor

Model MAC5501G

"V" TWIN STYLE PUMP RUNS COOLER AND PROVIDES 12.5 CFM AT 100 PSI

- Powerful Honda GX160 4-stroke engine for increased performance and superior reliability
- 10-gallon twin tanks provide air supply to multiple nailers
- Cast iron pump with Big Bore™ cylinder and piston is engineered to provide durability and faster recovery time for improved performance
- Industrial-grade recoil starter with ergonomic grip and recoil rope design for faster, easier starts
- Automatic idle control engineered to reduce gas consumption and service life

PERFORMANCE



"V" Twin Style Pump runs cooler and provides 12.5 CFM at 100 PSI for faster recovery time

POWER



Powerful Honda GX160 4-stroke engine for increased performance and superior reliability

CAPACITY



10-gallon twin tanks provide air supply to multiple nailers

DURABILITY



Cast iron pump engineered to provide longer durability



PERFORMANCE YOU NEED

5.5 HP Gas Air Compressor

Model MAC5501G

FEATURES & BENEFITS

- "V" Twin Style Pump runs cooler and provides 12.5 CFM at 100 PSI
 - Powerful Honda GX160 4-stroke engine for increased performance and superior reliability
 - 10-gallon twin tanks provide air supply to multiple nailers
 - Cast iron pump with Big Bore™ cylinder and piston is engineered to provide durability and faster recovery time for improved performance
 - Industrial-grade recoil starter with ergonomic grip and recoil rope design for faster, easier starts
 - Automatic idle control engineered to reduce gas consumption and service life
 - 10" non-flat tire for easier job site portability
 - Pump is oil-lubricated for cooler running temperatures and reduced wear
 - Large automotive style industrial air filters for increased air intake and greater efficiency
 - Convenient oil drain valve at the front of the pump for easier access
 - Integrated control panel with oversized pressure gauges for easier visibility of tank and hose pressure
 - Lever-handle ball valve tank drain improves upon standard petcock design for easier maintenance and air tank release
 - Anti-vibration rubberized feet for less vibration and reduced "crawling" during use
 - Fully enclosed belt drive with large fly-wheel for more efficient cooling of the pump
 - Stainless steel braided discharge hose for increased corrosion resistance and durability
 - Low profile design for easier transport and storage
 - Oil sight glass for fast, easy and efficient maintenance
 - Two universal brass couplers for increased durability and reduced corrosion
 - Ideal for framers, roofers, siding installation, decking, fencing, farming, general contractors, rental industry and more
- *Maximum horsepower



Model MAC5501G

SPECIFICATIONS

Gas Motor	5.5 H.P.
Pump	Oil-Lubricated
Tank	10 Gallon
Performance	12.5 CFM @ 100 PSI
Maximun Pressure	130 PSI
Overall Length	46" (1,168 mm)
Net Weight	190 lbs (86.2 kg)

STANDARD EQUIPMENT

2 Ea. 1/4" Quick Coupler (10TT-8), Spark Plug (065-01404-80)

makita.ca



When SERVICE Counts - Choose Makita